



ORIGEN OREX ULTRA 15W-40

High performance HDD and PC Engine Oil

DESCRIPTION

ORIGEN OREX ULTRA 15W-40 CI-4/SL is a high-performance multipurpose engine oil, developed for both diesel and petrol engines. ORIGEN OREX ULTRA 15W-40 CI-4/SL is based on premium quality base stocks and advanced additive technology suitable for naturally aspirated and turbocharged diesel engines running on a wide range of diesel fuels, from HIGH S to Ultra Low S (ULSD).

APPLICATIONS

ORIGEN OREX ULTRA 15W-40 CI-4/SL is designed for high performance heavy duty diesel engines. Also suitable for petrol & diesel LCVs and passenger cars; ideal for service centres and fleet operators.

TECHNICAL CHARACTERISTICS

- High BN retention ensures exceptional engine cleanliness corrosion control.
- Exceeds all major OEMs and Industry Specifications (*VDS3 formal Approval*)
- Single oil to service a wide range of engines diesel and gasoline.

HEAVY DUTY : API CI-4/CH-4 ACEA E7 MB228.3 MAN M3275 MTU Type2 VOLVO VDS-3 (Formal Approval) JASO DH-1 GLOBAL DHD1 CUMMINS CES 20077/20078 MACK EO-N RENAULT RLD-2 CAT ECF2 DETROIT DIESEL 93K215 DEUTZ DQC III-18

PASSENGER CAR/LCV (Petrol & Diesel)

API SL/SJ ACEA A3/B4 MB 229.1

SAE	15W40
Density at 20°C kg.m-3	0.880
Viscosity at 40°C cSt	114
Viscosity at 100°C cSt	15.0
Viscosity Index	140
Flash Point	236
Pour Point	-36
TBN	10.5



1000lt



210lt



20lt



4x5lt



12*1lt



20*500ml



*MSDS available on request.

Version 12: April 26